

302. Specific Pollutant Limitations. No person shall discharge wastewater containing in excess of the following concentrations at the point(s) where such wastewater enters the sewerage system based upon a 24-hour by-flow composite sample. Multiple industrial wastewater discharges from a permitted facility may be combined in a flow weighted manner to determine compliance with the following limitations for a 24-hour composite sample. Present standards shall remain in effect until October 1, 1983 at which time they shall be replaced by the standards on "Exhibit A" immediately following this page.
- \* 303. Federal Categorical Pretreatment Standards. Upon the promulgation of the Federal Categorical Pretreatment Standards for a particular industrial subcategory, the Federal Standard, if more stringent than limitations imposed under this Ordinance for sources in that subcategory, shall immediately supercede the limitations imposed under this Ordinance. The Superintendent shall notify all affected Users of the applicable reporting requirements under 40 CFR, Section 403.12.
304. Modification of Federal Categorical Pretreatment Standards. Where the POTW achieves consistent removal of pollutants limited by Federal Pretreatment Standards, the POTW may apply to the Approval Authority for modification of specific limits in the Federal Pretreatment Standards. "Consistent Removal" shall mean the average of the lowest 50 percent of the removals measured according to paragraph (d) (2) of Section 403.7, 40 CFR 403 and shall mean a reduction in amount of a pollutant in the POTW's effluent or alternation of the nature of a pollutant during treatment at the POTW when measured according to the procedures set forth in Section 403.7 of (Title 40 of the Code of Federal Regulations, Part 403) - "General Pretreatment Regulations for Existing and New Sources of Pollution" promulgated pursuant to the Act. The POTW may then modify pollutant discharge limits in the Federal Pretreatment Standards if the requirements contained in 40 CFR, Part 403, Section 403.7, are fulfilled and prior approval from the Approval Authority is obtained.
305. POTW Right of Revision. The POTW reserves the right to establish by ordinance more stringent limitations or requirements on discharges to the wastewater disposal system if deemed necessary to comply with the objectives presented in Section 200 of this Ordinance.
306. Excessive Discharge. No User shall ever increase the use of process water or, in any way, attempt to dilute a discharge as a partial or complete substitute for adequate treatment to achieve compliance with the limitations contained in the Federal Categorical Pretreatment Standards, or in any other pollutant-specific limitation developed by the City or State. (Comment: Dilution may be an acceptable means of complying with some of the prohibitions set forth in Section 301, e.g. the pH prohibition). The POTW may impose mass limitations on Users who are using dilution to meet the Pretreatment Standards or requirements of this Ordinance.
307. Accidental Discharges. Each User shall provide protection from accidental discharge of prohibited materials or other substances regulated by this Ordinance. Where necessary facilities to prevent accidental discharge of prohibited materials shall be provided and maintained at the owner or user's own cost and expense. Detailed plans showing facilities and operating procedures to provide this protection shall be submitted to the POTW for review, and shall be approved by the POTW before construction of the facility. All existing Users shall complete such a plan by January 1, 1983. No user who commences contribution to the POTW after the effective date of this ordinance shall be permitted to introduce pollutants into the system until accidental discharge procedures have been approved by the POTW. Review and approval of such plans and operating procedures shall not relieve the industrial user from the responsibility to modify the user's facility as necessary to meet the requirements of this Ordinance. In the case of an accidental discharge, it is the responsibility of the user to immediately telephone and notify the POTW of the incident. The notification shall include location of discharge, type of waste, concentration and volume, and corrective actions.

\* Exhibit A - on reverse side of this page